

AMBULANCE DOMELIGHT



ADVANCED LIGHTING FOR CRITICAL NEEDS

When the right light makes the difference, Ibis Tek is here to offer the right solution. The Ibis Tek Ambulance Domelight is AMEDD tested and proven to optimize illumination for medical needs. The specially designed light offers both bright, white natural and blue/green light for blackout mode operations.

Low power consumption, high efficiency LED based technology

Bright, uniform beam pattern controllable with low setting, high setting and blackout mode

Fully tested to meet US Military requirements for medical lighting requirements

AMBULANCE DOMELIGHT

SPECIFICATIONS

Width	6.34" (161mm)
Height	9.34" (237mm)
Depth	2.25" (57.3mm)
White Light Source	White LED
Color Light Source	~508nm LED
White Mode Current	2.3 Amps
Color Mode Current	0.5 Amps
Voltage	28 V
White light Output	160 fc
Weight	3.6 lbs
Lifetime	20,000 Hrs. +



- | Rugged
- | Reliable
- | Easy to install
- | Simple to operate

Environmental Specifications

Storage Temperature	-50 to 85°C
Operating Temperature	-50 to 85°C
Altitude (Operational)	Sea Level to 50,000 ft. +
Altitude (Non-Operational)	-15,000 ft. to 60,000 ft. +
Storage Humidity	95% (50°C) to 85% (38°C)
Operating Humidity	5% to 100% relative humidity
Vibration (Operational)	MIL-STD-810G, 514.6
Shock (Operational)	MIL-STD-810G, 516.6



| Black out

| Low Setting

| High Setting

IBIS TEK

912 Pittsburgh Road | Butler, PA 16002

P: 724.586.6005 | F: 724.586.6010

E: info@ibistek.com

www.ibistek.com